

MON24-CDS

24" TFT Full HD 16:9 Capacitive Touch Monitor with 1x USB, 1x COM, 1x VGA, 1x DVI-D and 1x DisplayPort, 9V~48V

FEATURES

24" TFT Full HD 16:9 LCD with Projected Capacitive Touch
Max. Resolution1920x1080

Designed with Aluminum Die-Cast Front Frame IP65 Compliant Front Panel

1x USB, 1x COM, 1x VGA, 1x DVI-D, 1x DisplayPort, 1x Audio

Built-in Two 5W Internal Speakers Convertible Display System (CDS) Supported Supports Panel / VESA / Rack Mounting OPTION! (Resistive 5-wire Touch / Glass) 9~48VDC via 3-pin Terminal Block







MON24-CDS

SPECIFICATIONS	
Operating Temp.	Ambient with air flow: -5°C to 60°C (With extended temperature peripherals; Ambient with air flow According to IEC60068-2-1, IEC60068-2-2, IEC60068-2-14)
Approval	EMC: CE, FCC Class A
Forsyning	Power Requirement: 9~48VDC Connector 3-pin Terminal Block Connector Power Adaptor Optional AC/DC 12V/5A, 60W Power Adapter
Kontrast	5000:1
LCD	24" 16:9
Lyd	AMP 5W + 5W (Internal Speaker)
Montering	vesa, panel, (oPTION raCK MOUNT NEED TO ORDER kit!)
OSD	LCD On/ LCD Off, Auto, Menu, Up and Down (Multi-language)
Synsfelt	178/178
Weight	kg. 7,76







