

L-CON10TC60

L-con controller with 10 x analog input and 6 x digital output. Also for thermocoupler sensors, PoE FEATURES

Intelligent Controller with Web Server
Logical functions, such as: IF-THEN-ELSE
No programming. Just select, click and finish
Supporter: I/O module, counter, hour, e-mail
Modbus / TCP protocol for SCADA software
Seamless integration
IEEE 802.3af compatible power over Ethernet (PoE)
1 x RJ45 - 100Mbit Ethernet
7 x Analog input: 0 - +/-2.5V, 0 - 20mA (ext. Resistors)
A/I Resolution: 16bit
10 Samples per Second
A/I Also to Thermocouller: J, K, T, E, R, S, B, B, C, L, M, LDIN43710
6 x Digital Output: 0 - + 50VDC / 700mA Open Collector
Supply voltage: POE or 12 - 48VDC / 4.5Watt



Danbit A/S Schous plass 1 Oslo, N-0552
Norway



67 104 460



salg@danbit.dk

SPECIFICATIONS

Operating Temp.	:	- 25°C - 75°C
Forsyning	:	12 - 48 VDC via klemrække eller via PoE
Indgang	:	10 stk. differentialindgange til termoelementer Opløsning 16 bit nøjagtighed $\pm 0,1 \%$, drift ± 25 ppm/°C Termoelementer J, K, T, E, R, S, B, N, C, L, M, LDIN43710 Leveres med terminalkort Status for afbrudt termoelement
Isolation	:	Optisk 2500 VRMS til analoge og digitale ind- og udgange i forhold til strømforsyningen. Magnetisk 1500 V fra netværksinterface til strømforsyningen
Netværk	:	10/100 Mbit m/RJ45 hunstik
Protokol	:	Understøtter Modbus/TCP
Udgange	:	6 stk. open collector 5 - 50 V 700mA
Dimensioner	:	123 x 72 x 35 mm

