

L-CON modul med digitale udgange FEATURES

Intelligent Controller with Webserver
Logical functions such as: IF-THEN-ELSE
No programming. Just pick, click and finished
Supports: I/O module, counter, timer, email
Modbus/TCP protocol to SCADA software seamless integration
IEEE 802.3af compliant Power over Ethernet (PoE)
1 x RJ45 - 10 / 100Mbit Ethernet
8 x Power relay output, COM NO
Relay switch: 30VDC, 250VAC 5A, only resistive load
Supply voltage: PoE or 12 - 48VDC / 5.5Watt



SPECIFICATIONS

Operating Temp.	:	- 25°C - 75°C
Forsyning	:	12 - 48 VDC via klemrække eller via PoE
Isolation	:	Optisk 2500 VRMS til analoge og digitale ind- og udgange i forhold til strømforsyningen. Magnetisk 1500 V fra netværksinterface til strømforsyningen
Netværk	:	10/100 Mbit m/RJ45 hunstik
Protokol	:	Understøtter Modbus/TCP
Udgange	:	8 stk. relæudgange type A (slutte) AC: 250 V og 5 A DC: 30 V og 5 A Lukketid er 6 ms og åbnetid er 3 ms
Dimensioner	:	123 x 72 x 35 mm



Danbit A/S Schous plass 1 Oslo, N-0552
Norway



67 104 460



salg@danbit.dk