

L-CON modul med digitale ind- og udgange FEATURES

- 1 x RJ45 - 10/100 Base-TX Ethernet
- Can be powered from a PoE
- Integrated Web Server Setup
- Logical functions with IF-THEN-ELSE Rules, I / O, CGI counter, Timer, etc.
- Email setup via Web browser
- Modbus / TCP Protocol to 6 x Digital input (Wet Contact - external voltage for High)
- Digital input has 16 bits counter
- 6 x Relay Power Output: 5A at 30VDC / 250VAC
- Power over Ethernet (PoE) or an external DC power supply
- Supply voltage: PoE or 12 - 48VDC / 5Watt
- temperature range -25 ° C ~ + 75 DEG C



SPECIFICATIONS

Operating Temp.	:	- 25°C - 75°C
Forsyning	:	12 - 48 VDC via klemrække eller via PoE
Indgang	:	6 stk. Kontakt indgange Logisk 0: maks. 4 V Logisk 1: 10 - 50V Med 16 bit tæller funktion maks. 50 Hz
Isolation	:	Optisk 2500 VRMS til analoge og digitale ind- og udgange i forhold til strømforsyningen. Magnetisk 1500 V fra netværksinterface til strømforsyningen
Netværk	:	10/100 Mbit m/RJ45 hunstik
Protokol	:	Understøtter Modbus/TCP
Strømforbrug	:	4.8 W
Udgange	:	6 stk. relæudgange type A (slutte) AC: 250 V og 5 A DC: 30 V og 5 A Skiftetider Lukke/åben 6 ms / 3 ms
Dimensioner	:	123 x 72 x 35 mm

