

L-CON Controller with 7 x Temperature sensor input,
2/3 wire Pt100, Pt1000, Ni120, CU100, Cu1000, 1 x
RJ45 Ethernet, PoE

FEATURES

Intelligent Control Controller with Webserver
 Logical functions such as: IF-THEN-ELSE
 No programming. Just pick, click and finished
 Supports: I / O module, counter, timer, email
 Modbus / TCP protocol to SCADA software seamless
 integration
 IEEE 802.3af compliant Power over Ethernet (PoE)
 1 x RJ45 - 10 / 100Mbit Ethernet
 7 x Temperature sensor inputs (differential)
 2/3-wire Pt100, Pt1000, Ni120, CU100, Cu1000
 A/I resolution: 16bit
 12 samples per second (Total)
 Individual sensor configuration
 Power supply: PoE or 12 - 48VDC / 4.5Watt



SPECIFICATIONS

Operating Temp.	:	- 25°C - 75°C
Forsyning	:	12 - 48 VDC via klemrække eller via PoE
Isolation	:	Optisk 2500 VRMS til analoge og digitale ind- og udgange i forhold til strømforsyningen. Magnetisk 1500 V fra netværksinterface til strømforsyningen
Netværk	:	10/100 Mbit m/RJ45 hunstik
Protokol	:	Understøtter Modbus/TCP
Dimensioner	:	123 x 72 x 35 mm

