

4 channel voltage data logger w/Graphic display. +/- 300mV to +/- 24volt. Each channel is isolated.
480,000 in memory

FEATURES

- 4 channel data logger with display
- External memory with SD slot
- USB port for PC
- input: DC to 100Hz
- +/- 0.3 Volt to +/- 24 volts
- 2ms Log -Interval with 10 Microvolt resolution
- Log intervals: 2 MS to 60 minutes
- Number of log intervals: 23
- Daisy-Chain 4 x Log-MCR4V
- Battery operation: 4 days to 130 days, dependent on logging
- External power supply: Micro-USB adapter (not incl.)



SPECIFICATIONS

USB	:	USB tilslutning til overførelse af målte data til PC
Operating Temp.	:	0 - 50 °C
Andet	:	4 enheder kan kobles sammen så der kan logges på 16 kanaler. Tilslutning af signaler der skal måles er via klemmeterterminaler. Med avancerede funktioner til dataopsamling og -lagring, grafisk visning m.m.
Forsyning	:	Batterier 2 stk. AA eller via USB maks. 250mA
Indgang	:	4 stk. differentielle impedans 1,1 MΩ
Måleområde	:	±24 V; ±6 V; ±1,5 V ±0,3 V maks. ±50V
Nøjagtighed	:	±0,3 %
Opløsning	:	Ved 24V 2.4mV, 6 V 0,6mV, 1,5 V 0,3mV og 300mV 0,06mV. 50-60 Hz Filter til: 0,01 mV. 50-60 Hz Filter fra: 0,1 mV
Skærm	:	Display til visning af loggende og aktuelle måle data, ved visning kan data skalere til f.eks. en temperatur
Software	:	Windows 2000, XP, Vista, Win7 og Win8

