

## 10.1" LCD Touch Screen Alu Front, Projected Capacitive Touch 1280x800 16:10, IP66 Front, DC 9 ~ 36V

### FEATURES

- 10.1" TFT 1280x800 (16:10)
- Front panel IP66 Standard / IP69K Option
- Aluminum cabinet
- VGA, DVI, HDMI and DP Input
- Supply voltage: DC 9 ~ 36V
- Contrast : 800:1
- Brightness: 350 Nits Standard / 1000 Nits Option
- Touch Via USB: Projected Capacitive Standard /  
Resistive Option / No Touch Option
- Touch Via RS232: Option
- VESA 100 and Panel Mount
- Dimensions: 285 x 189 x 48.9mm
- Weight: 1.9 kg
- Operating temperature: 0 ~ +50°C Standard / -20  
~ +60°C Option



## SPECIFICATIONS

|               |   |                                                       |
|---------------|---|-------------------------------------------------------|
| Andet         | : | 15G peak acceleration (11 msec. duration) / Operation |
| Drivere       | : | eGalaxTouch                                           |
| Forsyning     | : | DC 9 ~ 36V                                            |
| Indgang       | : | USB                                                   |
| IP-Tæthed     | : | IP66 front                                            |
| Kabinet       | : | Aluminum die-casting chassis                          |
| Montering     | : | Panel and VESA                                        |
| Opløsning     | : | 1280x800 16:10                                        |
| OS SUPPORT    | : | Windows XP, Vista, 7, 8, CE, Mac og Linux             |
| Touch         | : | USB, PCAP                                             |
| VESA standard | : | 100 x 100mm                                           |
| Weight        | : | 1.9 kg                                                |



MON10.1-TFT-T

## SPECIFICATIONS



Danbit A/S Schous plass 1 Oslo, N-0552  
Norway



67 104 460



salg@danbit.dk