

4 x Isolated RS422 / 485 serial ports, PCI DOS, Win 7 (32BIT) Linux support Korenix JETCARD 1404I FEATURES

REMAINDER SALE

JetCard 1404i 4 x isolated RS422-485

With 2 KV optical isolation

US SUPPORT

Windows 98/Me/NT/2000/XP/2003, Win 7 32bit

Linux RedHat Enterprise 4.0 (2.6.9)/RedHat

Enterprise 3.0 (2.4.21)

RedHat 9.0 (2.4.20)/RedHat 8.0 (2.4.18)/RedHat 7.3
(2.4.18)

RedHat 7.2 (2.4.7)/FC5(2.6.16)/FC3(2.6.9)/

FC2(2.6.5)/FC1(2.4.22)

Mandrake 10.1(2.6.8)/Mandrake 9.2 (2.4.22)

Regulat



SPECIFICATIONS

Baudrate	:	50 bit/s ~ 921,6 Kbit/s
Drivere	:	Windows 98, Me, NT, 2000, XP, 2003 og Vista
Duplex	:	Point-to-point fuld duplex eller multidrop halv duplex (Kortet understøtter automatisk flow control)
Høj/lav profil	:	Høj bagplade
Isolation	:	2 KV optisk isolation og 15 KV ESD beskyttelse
Porte	:	2-4 porte til enten RS422 eller RS485. Op til 4 kort kan monteres i samme system (giver 8-16 porte i alt)
Signaler	:	RS-422: TxD+/-, RxD+/-, RTS+/-, CTS+/-, GND (4-tråds) RS-485: Data+/-, GND (2-tråds)
Spænding	:	3.3 og 5 V PCI
Stik	:	1 x DB37 hunstik (100 cm kabel med 1 x DB37 hanstik og 4 x DB9 hanstik medfølger)
Strømforbrug	:	Maks. 590 mA (+5 V)
Terminering	:	Ingen terminering nødvendig, da termineringsmodstande (120 Ω) er indbygget
UART	:	16C950 kompatibel

