

Wireless RS232 connection via Bluetooth - as a set.
Up to 100 meters between the two RS232 ports.

FEATURES

- Wireless RS232 link between 2 RS232 ports.
- Only supplied as a set (2 pcs.).
- BT Ver 2.0+EDR, Class1
- Up to 100 meters with included antennas at line-of-sight
- Up to 1km with larger external antennas (additional purchase)
- Automatic establishment of connection at power on
- With frequency hopping to avoid interference
- Baud rate: 1200 - 921.6kbps, 8 data bits, O/E/No, 1/2 stop bit
- Setting up Baud rate etc. with DIP switches
- RTS/CTS on/off - DTR/DSR/DCD loop-back
- Supports multi-connection: 1 master to 4 slaves
- Supply voltage: 5 - 12VDC/80mA



SPECIFICATIONS

Forsyning	:	Får strøm via medfølgende USB kabel eller 230 VAC adapter. 5 - 12 VDC (maks. 80 mA v/5 VDC)
Frekvens	:	Frekvensbånd: 2.402 ~ 2.480 MHz, frekvens hop: 1.600 gange/sek.
OS SUPPORT	:	Uafhængig af styresystem, kræver ingen drivere
Rækkevidde	:	Op til 100 meters rækkevidde ved frit sigte og medfølgende antenner. Op til 1.000 meter ved anvendelse af større retningsbestemt antenne.



Danbit A/S Schous plass 1 Oslo, N-0552
Norway



67 104 460



salg@danbit.dk