

2 Ports serial port server, 2 x RS232 / 422/485, LAN and WiFi. Serial Device Server over Ethernet. 9 - 48VDC.

## FEATURES

External COM ports via Ethernet and Internet  
Serial device server to RS232/422/485 with WIFI



## SPECIFICATIONS

|                 |   |                                                                                                                                                                              |
|-----------------|---|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Administration  | : | Indstilles over netværk via http, Telnet konsol eller Windowsprogram                                                                                                         |
| Operating Temp. | : | -10 – 60 °C                                                                                                                                                                  |
| Kabinet         | : | IP50-tæt metalkabinet i format 47 x 110 x 90 mm (H x B x D)                                                                                                                  |
| Montering       | : | DIN skinne                                                                                                                                                                   |
| Porte           | : | To serielle porte, der kan bruges frit som RS232, RS422 eller RS485.<br>Hastigheder fra 110 bit/s til 921 Kbit/s, Databit:5/6/7/8, Stopbit:1/2. Paritet:<br>Lige/Ulige/Ingen |
| Protokol        | : | Pv4, ICMP, TCP, UDP, DHCP Klient, SNMP, SMTP, HTTP, DNS, NTP, RADIUS,<br>RFC2217, WPS                                                                                        |
| Signaler        | : | RS232: TxD, RxD, RTS,CTS, DTR, DSR, DCD, GND. RS422: TxD+, TxD-, RxD+,<br>RxD-, GND. RS485 2-leder: Data+, Data-, GND. RS485 4-leder: TxD+, TxD-,<br>RxD+, RxD-, GND         |
| Software        | : | COM driver til Windows XP, 2003, Win 7 32/64 bit og Win 8                                                                                                                    |
| Stik            | : | Serielle porte: 2 x DB9 han. Ethernet: 1 x RJ45 hunstik og 1 x R/SMA stik til<br>medfølgende antenne                                                                         |
| Strømforsyning  | : | 9 ~ 48 VDC via terminalblok (forbrug under transmission ca. 5,85 watt).<br>Leveres uden strømforsyning benyt DC24V625MA-D                                                    |

