

2 x Analog to Load Cell, +/- 2.5V, 0-20mA, 1 x Excitation like cell, 2x digital zoom, 2 x Digital Output (OC). LAN with PoE

FEATURES

FEATURES

- Built-in Web server
- Web HMI
- Modbus TCP and Modbus UDP protocols
- Good communication security
- Dual Watchdog
- Operating temperature range: -25 to +75°C
- I/O pair connection mirrors input to second output
- 2 x AI to load cell
- 1 x load cell excitation voltage out
- 2 x Digital out with counter
- 2 x Digital out (Open Collector)
- Supply voltage: 10 - 30VDC / 3watt



SPECIFICATIONS

Forsyning	:	10 - 30 VDC, 5,3 W via klemrække eller PoE
Indgang	:	2 stk. analoge differentialindgange: ± 15 mV, ± 50 mV, ± 100 mV, ± 500 mV, ± 1 V, $\pm 2,5$ mV, 0 - 20mA, 4 - 20mA og ± 20 mA
Indgang	:	2 stk. digitale: Logisk 0: 0-1 VDC og Logisk 1: 3,5-50 VDC
Netværk	:	10/100 Mbit m/RJ45-stik
Protokol	:	Modbus/TCP, TCP/IP og UDP
Software	:	Leveres med konfigureringssoftware til Windows 2000, XP, Vista, WIN7/8/10
Tæller	:	Digitale Indgange kan virke som 32 bit tæller, maks. frekvens 100 Hz

