

PCI Express card for USB 3.1C. PCIE card with USB3.1C

FEATURES

- PCI Express Base Specification Revision 3.0 single lane (x1).
- Compliant with the Universal Serial Bus 3.1 specification Gen2.
- Compliant with xHCI (eXtensible Host Controller Interface) specifications Revision 1.1
- Supports simultaneous operation of multiple USB 3.1, 3.0, USB 2.0 and USB 1.1 devices
- Supports USB data transfer rate of 10G/5G/480/12/1.5Mbps.
- Expands a single external USB 3.1 Super Speed plus Type-C port (DFP) on the system.
- The USB port provides a maximum of +5V DC / 3000mA power output to USB device.
- Built-in overcurrent protection on each USB port.
- Supports the device's remote wake-up function from USB keyboard or mouse.
- The hot swapping feature allows you to connect/disconnect a device without turning off the system.
- Driver support for Microsoft Windows 7, 8.x and 10 operating systems
- Certified with electromagnetic compatibility CE, FCC, VCCI, C Tick, BSMI and RoHS approval.
- Windows 11 64bit
- Windows 10 32/64 bit
- Windows 8.1 32/64 bit
- Windows 8.0 32/64 bit
- Windows Server 2022 64bit
- Windows Server 2019 64bit
- Windows Server 2016 64bit
- Windows Server 2012 R2 64-bit
- Windows Server 2012 64bit



**DANBIT**

CNV-PCIE-USB3.1C

SPECIFICATIONS

OS SUPPORT	:	Windows 7, 8, 10. Linux 2.6.31 eller nyere
Porte	:	1x USB 3.1C



Danbit A/S Schous plass 1 Oslo, N-0552
Norway



67 104 460



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.