

17 "Panel PC with steel front, Intel Core i3 / i5 / i7
with 2x PCIe expansion (can be delivered with
1000nits)

FEATURES

- 17" TFT-LCD 1280x1024
- Panel mounting
- Touch: Standard projected capacitive, on order: Resistive or glass
- Contrast 800:1 standard (on order: 1000:1 nits)
- 8th generation Intel Core Celeron, I3, I5, I7 support
- 1 x 260-pin DDR4 SO-DIMM socket up to 32GB 2400MHz
- 4x USB 3.0 type A
- 2x GbE LAN
- Sound in/out
- IP66 front
- 1 x HDMI
- 1 x VGA
- 2x 2.5" SATA RAID 0,1,5 support
- 3x COM (1xDB9 RS-232/422/485, 1x DB9 RS232, 1x DB9 RS-422/485)
- 1 x Mini PCIe full size (PCIe/USB/SATA)
- 1 x Mini PCIe half size (PCIe/USB)
- 1x SIM slot for (wifi/BT/4G)
- 1x PCIe1 and 1x PCIe x16 slot.
- 439x348x64.8mm
- CE/FCC Class A
- Working temperature 0~50 degrees
- Possibility of external ON/OFF via. 2-pole plug
- Wide range DC 9 ~ 36V power input
- Supports Windows 10 IoT, Windows 11



SPECIFICATIONS

USB	:	4 x USB 3.0 Type A, 2 x USB 2.0 Type A by cable (option)
Approval	:	CE / FCC Class A
Ethernet	:	2 x GbE LAN RJ-45
Forsyning	:	DC 9~36Vdc
IP-Tæthed	:	Front IP 66
Luftfugtighed	:	10 to 90% @ 40°C, non- condensing
Lyd	:	1 x Mic-in, Line-out
OS SUPPORT	:	WIN 7, Windows 8.1, Windows 10 IOT Enterprise
Porte	:	1xDB9 RS232, 1xDB9RS232/422/485, 1x RS422/485
Skærm	:	LCD Size 17" TFT-LCD Max. resolution 1280 x 1024 Max. color 16.7M Luminance(cd/m ²) 350 Viewangle(H°/V°) 170 (H) / 160 (V) Contrast 1000: 1 Backlight lifetime(hrs) 30,000 hrs
Temperatur	:	Operating temperature(°C) 0~50°C Storage temperature(°C)
Touch	:	Touch Type Resistive Touch Screen/Projected Capacitive Touch Screen Interface USB Light transmission(%) Over 80%(Resistive) / Over 90%(Projected Capacitive)



**DANBIT**

IPP17-I8+PCIEX

SPECIFICATIONS

Dimensioner : 439x348x95mm



Danbit A/S Schous plass 1 Oslo, N-0552
Norway



67 104 460



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.