

CNV-USB4UNI-I

Converter USB til 4xRS232/485, isoleret FEATURES

- USB 2.0 to 4 x RS232/422/485
- High-Speed serial ports 921.6kbps
- Driver for Windows, Linux, Mac OS X
- LEDs for Power and TxD/RxD activity
- ESD protection on USB and serial ports
- 2.5kV electrical isolation (ISO version only)
- Bus powered (non-ISO), Self powered (ISO version)
- Wide range of power input 9 - 54V DC
- Metal housing
- 19-inch rack and wall mounts
- Wide range of operating temperatures



Danbit A/S Schous plass 1 Oslo, N-0552
Norway



67 104 460



salg@danbit.dk

SPECIFICATIONS

Chipset	:	FTDI FT4232H Genesys GL850G
USB	:	USB 2.0 High Speed, USB 1.1 compliant
Operating Temp.	:	-25°C - 75°C
Baudrate	:	RS232: 180bps - 921.6/1000kbps, RS422: up to 12Mbps, RS485: up to 12Mbps
Input	:	5V (USB) or 9-54V Dcin
LED	:	TxD/RxD for each port
Luftfugtighed	:	5-95% non condensing
Montering	:	19-inch Rack or Wall mount
Porte	:	4 x RS232/422/485, 1 x USB type B
Standarder	:	CE, FCC
Dimensioner	:	196 x 147 x 44 mm

