

19 "DNV Marine Approved Panel Monitor, Supply 24Vdc, 5: 4 Format

FEATURES

- 19 "DNV2.4, IEC60945 Marine Monitor Without Touch
- 400 Nits
- IP66
- Resolution: 1280x1024 - 5: 4 Format
- Active Display Area: 376.32 (H) x 301.06 (V) mm
- 1 x composite (RCA phono)
- 1 x DVI-D
- 1 x S-Video (SVHS)
- 1 x RBG (D-SUB)
- Power Supply: Terminal block 24V DC
- Mounting: Panel (Flush) mount with IP66 *, VESA, Bracket mounting
- Anti vibration: 5Hz - 500Hz / 1Grms / 3Axis
- Anti shock: 15G, 11ms duration
- Optional: AC power signal Std IEC Inlet
- Optional: Touch Screen D-SUB 9P Female
- Optional: Remote Control via RS232 D-SUB 9P



SPECIFICATIONS

Operating Temp.	:	-15 ~ +55°C
Approval	:	DNV2.4,IEC60945,IACS-E10,CE,FCC
Betjening	:	Power On/Off via Front Button, VR Brightness Knob Control
Chok/Vibration	:	Anti-Vibration 5Hz~500Hz / 1Grms/3 Axis Anti Shock 15G, 11ms duration
Grafik	:	19", Res 1280 x 1024, Pixel Pitch (RGB) 0.294 (H) x 0.294 (V) Contrast Ratio 1000:1 (typ.) Brightness 400 (typ.) Viewing Angle -85~85 (H); -80~80 (V) Active Display Area 376.32 (H) x 301.06 (V) Max Colors 16.7M (8bits/ colors)
Indikatorer og kontakter	:	LED indicators Power Mode Status LED
IP-Tæthed	:	Front IP66, (saw touch IP54)
Luftfugtighed	:	5% to 95% (non-condensing)
Montering	:	Vesa, and stand (stand bracket is option)
OSD	:	On Screen Display control (OSD)
Skærm	:	19" Transflective
Strømforsyning	:	24Vdc DC Power Signal Screw terminal block





DANBIT

MON-MAR19"

SPECIFICATIONS

Weight : 5.4 Kg



Danbit A/S Schous plass 1 Oslo, N-0552
Norway



67 104 460



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.