

19" TFT, marine godkendt panel monitor med IP65 tæthed og touch

FEATURES

- 19" TFT marine touch monitor
- LED backlight
- 250 Nits
- 1 x HDMI, 1 x VGA, 1 x Composite, 1 x Audio3.5 Jack connector
- Anti-vibration: 5 - 500 Hz/1 Grms PTP
- Anti Shock: 15G/Peak (11ms)
- AC power standard IEC Inlet 100-240V AC
- Power On/Off via front buttons
- VR Brightness Knob adjustment
- Power Mode Status LED indicator
- On Screen Display control (OSD)
- Flush mount, VESA mount
- Optional: Available with Capacitive, SAW, IR Touch.
- Call to hear more
- Optional: AR Hardness Glass: 3mm Anti-Reflective Protect Glass
- Optional: DC Power: Isolate 12V/24V/48V/125V DC Power
- Optional: SR-BKT: Stand & Roof Mounting Bracket
- Optional: RT-BKT: Rotary Plate Robust Bracket
- Optional: SV-BKT: Sun-Visor Bracket



SPECIFICATIONS

Operating Temp.	:	0 - 50 deg. C
IP-Tæthed	:	IP65 tæthed
Montering	:	Panel (Flush) Mount, VESA Mount, Robust Bracket, Sun-visor Bracket
Strømforsyning	:	Standard IEC Type 100-240V AC
Weight	:	9.5 / 13 KGs
Dimensioner	:	483 x 444 x 70mm

