

## 4 x isolated digital input (counter) and 4 x relay output - DCON and Modbus RTU -25 ~ +75°C FEATURES

- 4 x Digital input and 4 x relay output
- Form A and Form C Power relay
- Source and Sink type of D/I
- D/I the entries is also 16-bit counter
- Configurable Power-on settings
- Configurable Safe Value setting
- Dual Watchdog
- Temperature range -25 to + 75 ° C
- Supply voltage: 10 - 30VDC
- DIN bracket



## SPECIFICATIONS

Operating Temp.	:	-25 - +75 °C
Baudrate	:	1200 ~ 115200 bps
Forsyning	:	10 ~ 30 VDC, 1.4 W
Indgang	:	4 x Digital input
Indgangsimpedans	:	10 kΩ
Interface	:	RS-485 Modbus RTU, DCON
Isolation	:	Intra-Module Isolation, Field-to-Logic 3750 VDC
LED	:	1 xLED as Power/Communication Indicator. I/O LED Indicators: 8 LEDs as Digital Input/Relay Output Indicators
Montering	:	Wall, DIN-Rail mount
Protokol	:	Modbus RTU: Slave, DCON: Slave
Stik	:	Screw Terminal
Tæller	:	Max Count 65535 (16-bit) Max. Input Frequency 100 Mhz Min. Pulse Width 5 ms



## SPECIFICATIONS

Watchdog	:	Yes
----------	---	-----

Dimensioner	:	72 mm (W) x 123 mm (H) x 35 mm (D)
-------------	---	------------------------------------



Danbit A/S Schous plass 1 Oslo, N-0552  
Norway



67 104 460



salg@danbit.dk