

M485-CNV232+I

RS232 for RS485 converter, 1200m, 115.2kBit / s,
3kV isolation on RS232 side, 10 - 30VDC, -25° -
+75°C

FEATURES

- Optoisolated RS-232 for RS485 converter
- 3kVDC isolation on RS232 from DC input
- ESD protection for RS232 / 485
- Baud rate 300 bit / s to 115,200 bit / s
- Supports power inputs of +10 V DC to +30 V DC
- Operating temperature: -25 ° to + 75 ° C
- For DIN rail mounting



Danbit A/S Schous plass 1 Oslo, N-0552
Norway



67 104 460



salg@danbit.dk

M485-CNV232+I

SPECIFICATIONS

Operating Temp.	: -25 °C ~ +75 °C
Afstand	: Op til 1,2 km på RS422/485-siden
Forsyning	: 10 - 30 VDC 1,2 W
Features	: Automatisk styring af TX Understøtter både halv og fuld duplex
Isolation	: 3000 VDC
Stik	: RS232 DB9 hun og RS422/485 samt forsyning skrueterminaler
Dimensioner	: (W x H x D) 72 mm x 118 mm x 35 mm



Danbit A/S Schous plass 1 Oslo, N-0552
Norway



67 104 460



salg@danbit.dk