

Industrial 2 x RS-422/485 PCI-Express Serial Card with Surge and Isolation Protection with High and Low Back Plate

FEATURES

2-port RS-422/485

Communication speeds up to 921.6 Kbps.

2KV overvoltage protection, IEC-61000-4-5 Level 3.

1.5KV insulated protection meets IEC-60747 -5-5

16C950 UART controller

RS-422 and RS-485 auto detection and switching technology

jumper and software free.

On-chip hardware automatic flow control to guarantee nothing data loss.

15KV ESD protection for all serial signals meets IEC-61000-4-2 standard.

Plug-n-Play, I / O address and IRQ assigned by BIOS.

Certified by CE , FCC, VCCI, BSMI, RoHS and Microsoft WHQL authentication.

Windows 11 24H2 64 bit

Windows 11 23H2 64 bit

Windows 11 22H2 64 bit

Windows 11 21H2 64 bit

Windows 10 22H2 (22H2) 32/64 bit

Windows 10 21H2 (21H2) 32/64 bit

Windows 10 21H1 (21H1) 32/64 bit

Windows 10 20H2 (20H2) 32/64 bit

Windows 10 20H1 (2004) 32/64 bit

Windows 11 IoT Enterprise 24H2

Windows 11 IoT Enterprise LTSC 2024

Windows 11 Enterprise LTSC 2024

Windows 10 IoT Enterprise 22H2

Windows 10 IoT Enterprise 21H2

Windows 10 IoT Enterprise LTSC 2021

Windows 10 Enterprise LTSC 2021 32/64bit

Windows Server 2022 64bit



SPECIFICATIONS

Andet	:	Option: PCIe card holder ask for price!
Beskyttelse	:	±15KV ESD IEC-61000-4-2 Air Discharge ±8KV ESD IEC61000-4-2 Contact Discharge ±4KV ESD IEC61000-4-2 Level 2 Line-to-Line 2KV Surge IEC61000-4-5 Level 3 Surge Immunity Test 1.5 KV Isolation IEC60747-5-5 Hi-Pot
FIFO	:	128byte Hardware
Hastighed	:	50bps ~921.6Kbps, Stop bit 1, 1.5,2, Parity even,odd,none,mark,space
Kabel	:	DB44 til 4 x DB9 male , 40CM
PCI	:	PCI express 2.0 x 1 (single lan)
Porte	:	4 x RS422/485
Signaler	:	RS-422: TxD+, TxD-, RxD+, RxD-, GND 4-wire RS-485: TxD+, TxD-, RxD+, RxD-, GND 2-wire RS-485: Data+, Data-, GND
Stik	:	DB44 Female

