

19 "TFT monitor with 350-nits LCD, with electricity without touch, dust and leakproof IP66, Dual AC / DC inputs,

FEATURES

19 "TFT metal monitor LED backlight, IP66
1280 x 1024
350 nits, 1000: 1, 5: 4
Response time: 5ms
viewing angle: 170 ° / 160 °
3 x BNC
2 x DVI-I (29-pin DVI-D female)
1 x VGA (15-pin D-sub female)
1 x RS232 / 422/485 (software selectable terminal blocks)
100 to 240 VAC, 24 VDC (18 to 30 V)
-15 to 55 ° C (5 to 131 ° F)
weight: 9,700 g
483 x 444 x 82 mm
Panel mounting
RoHS, CRoHS, WEEE
Optional: RS-232: Tx, Rx, RTS, CTS, DTR, DSR, DCD, GND
Optional: RS-422: Tx +, Tx-, Rx +, Rx-, GND
Optional: RS-485-2w: Data +, Data, GND
Optional: RS-485-4w: Tx +, Tx-, Rx +, Rx-, GND



SPECIFICATIONS

Antal farver	:	16.7M (8-bit/color)
Betragningsvinkel	:	170°/160°
Forsyning	:	100 to 240 VAC, 24 VDC (18 to 30 V)
I/O	:	3 x BNC, 2 x DVI-I, 1 x VGA
Kontrast	:	1000:1, 350 nits, 5:4
Pixels	:	1280 x 1024
Porte	:	1 x RS232/422/485 (software valgt terminal blok)
Weight	:	9,700 g
Dimensioner	:	483 x 444 x 82 mm

