

7" Robust tablet for car mounting, capacitive multi-touch, 500 nits,

FEATURES

- Intel® Atom™ E3815 1.46GHz
- 2GB DDR3L SODIMM; mSATA and Micro SD slot
- 500 nits with auto-dimming
- Capacitive multi-touch (PCT)
- 5 x programmable buttons
- 2 x volume adjustment buttons
- 1 x RS-232, 1 x RS232/422/485
- 2 x USB (3.0, 2.0)
- 1 x Dual Micro SIM slot
- 1 x CAN bus (SAE J1939 supported)
- 1 x Gigabit Ethernet (RJ45)
- IEC 60529 IP65 (except bottom I/O)
- Vibration (during operation) : MIL-STD-810G, Method 514.7 c2/c3/c4
- Shock (during operation) : MIL-STD-810G, 40G at 11ms Terminal / Sawtooth
- 30°C to +60°C
- 9~36 VDC input
- Vehicle power protection (ISO 7637-2)
- Windows 10 IoT



SPECIFICATIONS

CPU	:	Intel® Atom™ E3815 1.46GHz
Operating Temp.	:	-30°C to +60°C
Batteri	:	UPS backup battery
Harddisk	:	mSATA and Micro SD slot
Hukommelse	:	2GB DDR3L SODIMM
I/O	:	1 x RS-232, 1 x RS232/422/485 2 x USB (3.0, 2.0) 1 x Dual Micro SIM slot 1 x CAN bus (SAE J1939 supported) 1 x Gigabit Ethernet (RJ45)
IP-Tæthed	:	IEC 60529 IP65 (except bottom side I/O)
Kontrast	:	500 nits support auto-dimming
Netværk	:	Gigabit Ethernet (RJ45)
Skærm	:	7" WSVGA TFT LCD (1024 x 600)
Touch	:	Capacitive multi-touch (PCT)

