

## 7 ports industrial PoE + gigabit unmanaged switch, 4 x RJ45, 2 x SFP

### FEATURES

- 4 x 10/100 / 1000Tx IEEE 802.3at PoE + Compliant with 30W per Port
- 1 x 10/100 / 1000Tx & nbsp;
- 2 x 100/1000 SFP
- Auto MDI / MDI-X Function < br> 14Gbps Back-Plane (Switching Fabric)
- 8K MAC Address
- 9.6Kbytes Jumbo Frame
- Surge Protection: 2,000 VDC
- ESD Protection: 6,000 VDC
- Power Supply: 12 ~ 36VDC
- Built-in 1 x Relay Output for Power Failure Detection
- IP30 Rugged Metal Case Design
- Your rail and wall mounting
- Operating temperature -40 ° to 75 ° C
- Dimensions: 46 x 99 x 142mm
- Weight : 1.4 Lb



## SPECIFICATIONS

|                 |   |                                                                                                                                               |
|-----------------|---|-----------------------------------------------------------------------------------------------------------------------------------------------|
| Operating Temp. | : | 40° to 75°C                                                                                                                                   |
| Approval        | : | EMI, EMS, RF, RF Radiation Exposure, EN60950-1 CNS14336-1, RoHS Compliant                                                                     |
| I/O             | : | 5 x RJ45 Ports w/ 4*10/100/1000Tx (PSE 30W/Port), and 1*10/100/1000Tx, 2 x 100/1000 SFP Slot                                                  |
| IP-Tæthed       | : | Metal, IP30 protection                                                                                                                        |
| Luftfugtighed   | : | 5 to 95%, (non-condensing)                                                                                                                    |
| Montering       | : | Din skinne og væg montering                                                                                                                   |
| Netværk         | : | 10Base Tx: 2-pair UTP/STP Cat. 3,4,5 100Base Tx: 2-pair UTP/STP Cat. 5 1000Base Tx: 2-pair UTP/STP Cat. 5/5E                                  |
| Standarder      | : | IEEE 802.3 10BaseTx Ethernet IEEE 802.3u 100BaseTx Fast Ethernet IEEE 802.3ab 1000BaseTx Ethernet IEEE 802.3z Gigabit Fiber IEEE 802.3at PoE+ |
| Strømforbrug    | : | 145 Watts                                                                                                                                     |
| Strømforsyning  | : | 12~36VDC, Redundant Input                                                                                                                     |
| Switch          | : | 14,880pps for Ethernet Port 148,800pps for Fast Ethernet Port 1,488,000pps for Gigabit Ethernet Port, 10Gbps Back-Plane (Switching Fabric)    |
| Weight          | : | Unit 1.4 lb. Shipping Weight 1.8lbs                                                                                                           |



**DANBIT**

ANR-LNP-0702G-F-24T

## SPECIFICATIONS



Danbit A/S Schous plass 1 Oslo, N-0552  
Norway



67 104 460



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.