

Stand alone thermal PT network camera, Temperature alarm, 400x300 pixels, anti frost FEATURES

Stand alone thematic network PT camera with
temperature alarm

17 different color adjustments

Micro SD card 128GB

Monitoring angle: H: 15.4 ° V: 11.6 °

can catch fire: 735m distance

Can pick up person: 735m distance

can pick up vehicle: 2255m distance

Can recognize fire: 245m distance

can recognize person: 184m distance

can recognize vehicle 564m distance

Main Stream: D1 @ 25 / 30fps

H.265, H.264, MJPEG

Operating temperature: -40 ° C ~ 60 ° C

RJ-45 (10 / 100Base-T)

Max 10 users

DC12V / POE / AC24V

IP66, metal

Dimensions: 585 × 251 × 502mm

Weight: 22.5Kg (with 50mm lens)



SPECIFICATIONS

Operating Temp.	:	-40°C~60°C
Alarm	:	Over temperature alarm, Temperature difference alarm
Ethernet	:	RJ-45 (10/100Base-T), 1 Ethernet (10/100 Base-T) RJ-45 Connector
Features	:	Motion detection, Disk alarm, I/O alarm, Temperature alarm, Defog
Indgang	:	Max 10 brugere sammetid
Interface	:	RS485, BNC, Reset knap, RJ45
IP-Tæthed	:	IP66, MEtal
Kompression	:	H.265, H.264, MJPEG
Linse	:	Fixed, motorized focus, 25mm
Pixels	:	400x300
Protokol	:	IPv4/IPv6 ,HTTP,RTSP/RTP/RTCP, TCP/UDP, DHCP, DNS, PPPOE, SMTP, SIP ,802.1x
Strømforsyning	:	DC36V, Max 100W



**DANBIT**

KAM-TERMO-STAND

SPECIFICATIONS

Zoom : 16X digital zoom



Danbit A/S Schous plass 1 Oslo, N-0552
Norway



67 104 460



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.