

12-Port Industrial PoE + Gigabit Unmanaged Switch FEATURES

- 8 x 10/100 / 1000Tx RJ45 (30W / port)
- 2 x 10/100 / 1000Tx RJ45
- 2 x 100/1000 SFP Ports
- Auto MDI / MDI-X Function
- Store-and-Forward Switching Architecture
- 24Gbps Back-Plane (Switching Fabric)
- 8K MAC Address Table
- 9.6Kbytes Jumbo Frame
- Surge Protection: 2,000 VDC
- ESD Protection: 6,000 VDC > UL Class I, Division 2 Certified
- Power supply: 48 ~ 55VDC
- Built-in relay Output for Power Failure
- IP30 Rugged Metal Case Design
- DIN rail and Wall mounting
- Operating temperature STD: -10 ° to 70 ° C



SPECIFICATIONS

Operating Temp.	:	STD: -10° to 70°C
Buffer	:	7,926pps (default)
Chok/Vibration	:	IEC60068-2-32, IEC60068-2-27
Ethernet	:	10*10/100/1000Tx RJ45 (w/8*PSE: 30W/Port)
Fiber	:	2 x 10/100/1000 SFP Slot
Forbindelse	:	1 removable 6-contact terminal block
Luftfugtighed	:	5% to 95%, (non-condensing)
Montering	:	DIN-skinne og væg montering
Protokol	:	CSMA/CD
Standarder	:	IEEE 802.3 10BaseTx Ethernet IEEE 802.3u 100BaseTx Fast Ethernet IEEE 802.3ab 1000BaseTx IEEE 802.3z Gigabit Fiber IEEE 802.3at PoE+
Strømforbrug	:	10 Watts Full load w/PoE 215W@48V / 255W@51~55V
Strømforsyning	:	48-55VDC



**DANBIT**

ANR-LNP-1202G-SFP

SPECIFICATIONS



Danbit A/S Schous plass 1 Oslo, N-0552
Norway



67 104 460



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.