

12-port industrial Gigabit Switch with PoE +  
unmanaged. 8 x RJ45 ports and 4 x SFP ports,  
48-55VDC

## FEATURES

- 8 x 10/100 / 1000Tx RJ45 (30W / port)
- 4 x 100/1000 SFP Ports
- Auto MDI / MDI-X Function
- Store-and-Forward Switching Architecture
- 24Gbps Back-Plane (Switching Fabric)
- 8K MAC Address Table
- 9.6Kbytes Jumbo Frame
- Surge Protection: 2,000 VDC
- ESD Protection: 6,000 VDC
- Supply Voltage: 48 ~ 55VDC
- Built-in Relay Output to Power Failure
- IP30 Rugged Metal Case Design
- DIN Rail and Wall Mounting
- Operating Temperature STD: -10 ° to 70 ° C



## SPECIFICATIONS

|                 |   |                                                                                                                                         |
|-----------------|---|-----------------------------------------------------------------------------------------------------------------------------------------|
| Operating Temp. | : | -10° to 70° C                                                                                                                           |
| Buffer          | : | 7,926pps (default)                                                                                                                      |
| Chok/Vibration  | : | IEC60068-2-32, IEC60068-2-27                                                                                                            |
| Ethernet        | : | 8*10/100/1000Tx RJ45 (w/8*PSE: 30W/Port)                                                                                                |
| Fiber           | : | 4*100/1000 SFP Slot                                                                                                                     |
| Forbindelse     | : | 1 removable 6-contact terminal block                                                                                                    |
| Luftfugtighed   | : | 5% to 95%, (non-condensing)                                                                                                             |
| Protokol        | : | CSMA/CD                                                                                                                                 |
| Standarder      | : | IEEE 802.3 10BaseTx Ethernet IEEE 802.3u 100BaseTx Fast Ethernet<br>IEEE 802.3ab 1000BaseTx IEEE 802.3z Gigabit Fiber IEEE 802.3at PoE+ |
| Strømforbrug    | : | 15 Watts Full load w/PoE 215W@48V / 255W@51~55V                                                                                         |
| Strømforsyning  | : | 48-55VDC                                                                                                                                |
| Dimensioner     | : | 46 x 99 x 142 mm (W*D*H)                                                                                                                |

