

Media Converter Gigabit for single fiber and WDM mode, Multi Mode up to 550m, WDM-B, TX1550nm / RX1310nm, 5VDC

FEATURES

- IEEE 802.3 / u / ab 10/100 / 1000BaseT
- IEEE 802.3z 1000BaseX
- Jumbo Frame (9K bytes)
- Store-and-Forward Switching Mechanism
- Auto-Crossover for MDI / MDIX in TP Port
- Auto Negotiation in TP Port
- Flow Control
- Link Alarm
- Auto & Force Mode Configuration
- Dimensions: 71 x 94 x 26 mm for DC5 V, 1.5 A



SPECIFICATIONS

Operating Temp.	:	0° C to 50° C
Afstand	:	FCU-3002A-SC: 550 m FCU-3002A-SC-S1: 10 Km FCU-3002A-SC-S2: 20 Km FCU-3002A-WA/WB-S1: 10 Km FCU-3002A-WA/WB-S2: 20 Km
Interface	:	10/100/1000BaseT: 1 x RJ45 Port 1000BaseX: 1 x Port
IP-Tæthed	:	IP30
LED	:	Power, FDX, Status, Speed, FO Link/ACT, TX Link/ACT
Luftfugtighed	:	5% to 95% (non-condensing)
Montering	:	DIN skinne montering og væg montering
Standarder	:	IEEE 802.3z 1000BaseX IEEE 802.3 10BaseT IEEE 802.3u 100BaseTX IEEE 802.3ab 1000BaseT IEEE 802.3x Flow Control
Strømforbrug	:	3 Watts
Strømforsyning	:	External Power Supply: DC 5V, 1.5A
Weight	:	0.6 Kg

