

## 26-port industrial gigabit unmanaged switch, IP40, 1U, 19 "Rackmount

### FEATURES

- 24 x 10/100 / 1000Tx RJ45
- 2 x Gigabit Combo Ports
- 2 x 10/100 / 1000Tx RJ45
- 2 x 100/1000 SFP Slots
- Auto MDI / MDI-X Function
- Store-and-Forward Switching Architecture
- 8K MAC Address Table
- 9.6Kbytes Jumbo Frame
- Surge Protection: 2,000 VDC
- ESD Protection: 6,000 VDC
- Redundant Power Input Design: 90 ~ 264VAC
- 1 x Built-in Relay Output for Power Failure
- IP40 Rugged Metal Case Design
- 1U 19 "Rackmount Design Support
- Operating Temperature: -10 ° to 70 ° C



## SPECIFICATIONS

|                 |   |                                                                                                                             |
|-----------------|---|-----------------------------------------------------------------------------------------------------------------------------|
| Operating Temp. | : | STD: -10° to 70° C                                                                                                          |
| Approval        | : | EMI, EMS, FCC Part 15 Subpart B Class A, CE EN 55022 Class A                                                                |
| Buffer          | : | 4Mbps (buffer)                                                                                                              |
| Chok/Vibration  | : | IEC60068-2-27, IEC60068-2-6                                                                                                 |
| I/O             | : | 26 x RJ45 10/100/1000Tx, 2 x 100/1000 SFP Slots                                                                             |
| Luftfugtighed   | : | 5 to 95%, (non-condensing)                                                                                                  |
| Montering       | : | 1U 19" Rackmount                                                                                                            |
| Netværk         | : | 10Base Tx: UTP/STP Cat. 3,5 100Base Tx: UTP/STP Cat. 5 1000Base Tx: UTP/STP Cat.5/5e/6                                      |
| Protokol        | : | CSMA/CD                                                                                                                     |
| Standarder      | : | IEEE 802.3 10BaseT Ethernet IEEE 802.3u 100BaseTX Fast Ethernet IEEE 802.3ab 1000BaseT IEEE 802.3z 1000Base-X Gigabit Fiber |
| Strømforbrug    | : | 24Watt                                                                                                                      |
| Strømforsyning  | : | 90-264VAC/47-63Hz                                                                                                           |



**DANBIT**

ANR-LNX-2602G-SFP

## SPECIFICATIONS



Danbit A/S Schous plass 1 Oslo, N-0552  
Norway



67 104 460



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.