

10-port industrial unmanaged switch with 2 SFP ports
and 8 RJ45 ports.

FEATURES

- 8 x 10/100 / 1000Tx RJ45 IEEE 802.3at PoE + 2 x 100/1000 SFP Ports
- Auto MDI / MDI-X Function
- Store-and-Forward Switching Architecture
- 20Gbps Back -Plane (Switching Fabric)
- 8K MAC Address Table
- 9.6Kbytes Jumbo Frame
- Surge Protection: 2,000 VDC
- ESD Protection: 6,000 VDC
- UL Class I, Division 2 Certified
- Power Supply : 48 ~ 55VDC
- Built-in relay Output for Power Failure
- IP30 Rugged Metal Case Design
- DIN-Rail and Wall mounting
- Operating temperature STD: -10 ° to 70 ° C



SPECIFICATIONS

Operating Temp.	:	STD: -10° to 70°C
Ethernet	:	8 x RJ45 Ports w/10/100/1000Tx (PSE 30W/Port)
Fiber	:	2 x 100/1000 SFP Slot
Luftfugtighed	:	5 to 95%, (non-condensing)
Montering	:	DIN-skinne og væg montering
Netværk	:	10Base Tx: 2-pair UTP/STP Cat. 3,4,5 100Base Tx: 2-pair UTP/STP Cat. 5 1000Base Tx: 2-pair UTP/STP Cat. 5/5E
Protokol	:	CSMA/CD
Standarder	:	IEEE 802.3 10BaseTx Ethernet IEEE 802.3u 100BaseTx Fast Ethernet IEEE 802.3ab 1000BaseTx IEEE 802.3z Gigabit Fiber IEEE 802.3at PoE+
Strømforbrug	:	210 Watts @ 48V 250 Watts @ 51-55V (Full Load w/ PoE)
Strømforsyning	:	48~55VDC, Redundant Input
Dimensioner	:	46 x 99 x 142 mm (W*D*H)

