

HDMI Matrix over the network (IP), up to 24 transmitters and 96 receivers, 1080p @ 60Hz, Kit w/Receiver and Transmitter

### FEATURES

- HDMI Matrix over IP.
- Video Wall configuration
- Setup with DIP switches (TX-RX Pair)
- Max 24 transmitters and 96 receivers (contact us for buying TX or RX units separately.) < br> HDMI 1.3, HDCP 1.3.
- HDMI loop out to the local monitor
- Resolution 1080p @ 60/50/30/25 / 24Hz, 720p @ 60 / 50Hz.
- point to point over Cat 6. Maximum . 100meter.
- Point to many Hotels can be supplied via PoE (802.3af) or 12VDC 1A (PSU included).
- Power Consumption: 2.5W.
- Switch must support protocol: IGMP Snooping or IFMP.
- Delay: 120ms
- Operating temperature: 0 ~ 40 ° C.



## SPECIFICATIONS

Operating Temp.	:	0 - +40°C
Forsinkelse	:	Videosignal kan være forsinket ca. 120mS
Forsyning	:	12VDC, 1Amp
Lyd	:	2.1 channel stereo
Opløsning	:	Op til 1080p @60Hz
PoE	:	802.3af
Switch	:	Kan tilsluttes switch som supportere IGMP/IFMP snooping
Udvendige mål	:	125 x 84 x 25mm

