

500VA / 300W UPS for DIN rail, incl. 1 piece. 12V battery, line-interactive, 2-6 ms on time, True sine curve

FEATURES

UPS with DIN bracket for control panel, electrical cabinets, rack cabinet like.
Compact all-in-one to the DIN rail UPS 500VA / 300watt
Output voltage: 230VAC / 50Hz - genuine sine wave
Line-interactive means switching at power failure (2-6ms)
Nødforsynings time: 50% load for about 12 minutes
Noise level: Less than 40 dbA at 1 meter
output voltage is sine wave
4-6 hour recharge time to 90% capacity
Auto restart on mains supply restored
Battery: 1 pc. 12V / 7Ah - see manual for life
Dimensions: 250 x 135 x 115 mm | Weight with battery: 2.8 kg
Operating temperature: 0 - + 40 ° C



SPECIFICATIONS

Operating Temp.	:	0 - +40°C
Batteri	:	2 x 12V/7Ah
Batteri	:	Lithium-ion, indbygget
Kabinet	:	Metal, 2 x DIN-beslag, med blæser
Kapacitet	:	300Watt / 500VA
Mål og vægt	:	280 x 140 x 132 mm, 2,8 kg
Porte	:	RS485
Terminering	:	Skrueterminaler
Udgangsspænding	:	230VAC / 50Hz ægte sinuskurve

