

IP66 Industrial Keyboard with TouchPad, USB, Nordic, Low Profile Keys, 1.2mm travel, 3 x VESA FEATURES

Industrielt tastatur med touchpad

89 taster

FN+CLEAN låser taster under rengøring

IP66

USB, 5VDC/250mA

Nordisk layout

Hvid bagbelysning (NVIS compliant)

Kabellængde: 2m

Dimensioner: 297.5 x 192.0 x 22.5mm (B x D x H)

Temperatur:

Operating temperature: -30°C ~ +60°C

Storage temperature: -45°C ~ +70°C

Test:

Saline mist 96h, IEC60512-6

Damp heat test at +40°C : 21 days, IEC 60512-6

Dry heat test at +85°C : 10 days, IEC 60512-6

Operating RH: 100%

Atmospheric pressure: 60-106Kpa

Shock: 3 x 11 ms pulses of 50g on each of 3 axes

Vibration: MIL-STD 810G-POWER SPECTRAL

DENSITY: 0.04g/Hz, FREQUENCY RANGE: 20Hz -

2kHz, DURATION OF TEST PER

AXIS: 3 hours



SPECIFICATIONS

USB	:	USB-A Male
Operating Temp.	:	-30°C to +60°C
Farve	:	Black
Chok/Vibration	:	Shock: 3 x 11 ms pulses of 50g on each of 3 axes / Vibration: MIL-STD 810G-POWER SPECTRAL DENSITY: 0.04g/Hz, FREQUENCY RANGE: 20Hz - 2kHz, DURATION OF TEST PER AXIS: 3 hours
Features	:	Water Resistant
Kabel	:	2m
Materiale	:	Plastic
Tastatur/mus	:	Nordisk
Temperatur	:	-45°C to +70°C
Tilslutning	:	USB
Layout	:	Nordic
Dimensioner	:	297.5 x 192.0 x 22.5mm (B x D x H)

