

BOOST-HDMI120-U-4K-I

## HDMI KVM Extender 4K@30Hz up to 120 meters over RJ45 Patch cable, IR, 5VDC, USB 2.0 HID FEATURES

4K HDMI Extender Over IP
HDMI 1.4 / HDCP 1.4
Up to 120 meters (point-to-points)
4K @ 30 Hz
2 x USB-A 2.0 (HID emulation)
One-to-One or One-To-Many
Max 32 RX Can be connected One TX (Via Ethernet Switch)
Remote-IR from TX to RX

Plug and Play Power Supply: 5V 1A (2 included) Dimensions: 107 x 105 x 27 mm

Operating temperature: -15 - + 55 ° C

Weight: TX 499G, RX 494G

acquisition: K-USB4AM-AM -Fe to connect the USB-A

port to PC





BOOST-HDMI120-U-4K-I

			$\sim$ 1		A T I	NS
_	U	_		_		$\sim$
	_				 _	

USB : RX: 2 imes USB-A 2.0 (HID), TX: 1 imes USB-A 2.0 (for PC)

Operating Temp. : -15 - +55°C

Maks. afstand : 120m

Maks. opløsning : 4K@30 Hz

Strømforsyning : 5V 1A (2 pcs included

Weight : TX 499g, RX 494g

Dimensioner :  $107 \times 105 \times 27 \text{ mn}$