



DANBIT

BARCCD2D-IP66

Industrial Panel Mount 1D and 2D (Barcode/QR)
Scanner, IP66 tight, USB, white light, fast reading

Quick installation (no screws needed)
Can read QR and barcode from your phone's screen!
Supports most 1D and 2D formats
USB1.1, HID-KBW, HID-POS, Custom HID
RS232 (optional)
High speed
Choice of colored light when reading code
IP66-tight
90ms read speed
Reading distance: 0 to 11 cm
Summer
OS Support: Win XP/7/8/10, Android, Linux, Mac.
Operating temperature -20 to 70 degrees
Dimensions 101.5 x 78.5 x 48 mm (hole cutout 640x480 mm)
Print contrast min. 25%
5VDC with special power connector! ("-" is center, "+" is side)



Danbit A/S Schous plass 1 Oslo, N-0552
Norway



67 104 460



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.

BARCCD2D-IP66**SPECIFICATIONS**

Forsyning	:	5 ~ 12VDC
Interface	:	USB eller RS232 (option)
IP-Tæthed	:	IP66
Læseafstand	:	0 ~ 11cm
Læsehastighed	:	90ms
Opløsning	:	640 x 480
Stregkoder	:	1D og 2D
Dimensioner	:	101,5 x 78,5 x 48 mm (hul udskæring 640x480mm)



Danbit A/S Schous plass 1 Oslo, N-0552
Norway



67 104 460



salg@danbit.dk