

KAM-2M-STEEL

2 Mega Pixel bullet IP camera, Anti corrosion, Steel housing, IP68 / IP69, -40°C - +65°C

## FEATURES

- 316L Stainless Steel Housing
- Anti-corrosion
- NEMA-4X, IP68/ IP69
- 2 Megapixel IR Bullet IP Camera
- H.264+/ H.264/ M-JPEG Compression
- Smart Focus System for Remote Focus Adjustment
- Digital Noise Reduction
- Power over Ethernet
- Day Night Manual Switch Time Control
- Operating Temperature -40°C~65°C with Heater
- IR LED Built-in 45M/span
- IR Cut Filter Mechanism
- Micro SD Card Backup
- 2-way Audio
- Support iPhone/Android/Mac
- SDK for Software Integration
- Free Bundle 36 Ch Recording Software



Danbit A/S Schous plass 1 Oslo, N-0552  
Norway



67 104 460



salg@danbit.dk

## SPECIFICATIONS

|                 |   |                                                                                                                                                                                                                        |
|-----------------|---|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Operating Temp. | : | -40°C~70°C                                                                                                                                                                                                             |
| I/O             | : | D1x1, D0x1, RJ45, DC JACK, BNC Output, Micro SD card slot built-in (optional)                                                                                                                                          |
| IP-Tæthed       | : | IP68, IP69                                                                                                                                                                                                             |
| Linse           | : | 2.8-12mm 4.2X Bulid-in Zoom Lens @ F1.4                                                                                                                                                                                |
| Lyd             | : | Audio Format G.711 (64K) / G.726 (32K, 24K) Audio Input: External line in<br>Output: External line out Support 2 way audio                                                                                             |
| Lysfølsomhed    | : | Color 0.005 lux, (AGC ON)                                                                                                                                                                                              |
| Opløsning       | : | 1920x1080@30fps 1280x720@30fps 640x360@30fps (2M)                                                                                                                                                                      |
| PoE             | : | Max:8.16W(IR ON), 3.36W(IR OFF)                                                                                                                                                                                        |
| Protokol        | : | IPv6, IPv4, HTTP, HTTPS, SNMP, SSL, TLS, DNS, ICMP, IGMP, ARP, SNTP, QoS/DSCP, IEEE 802.1X, RTSP/RTP/RTCP, TCP/IP, UDP, SMTP, FTP, PPPoE, DHCP, DDNS, NTP, UPnP, SAMBA, Bonjour, Google Drive, Dropbox, ONVIF Profiles |
| Sensor          | : | 1/2.8" Sony True WDR Starvis CMOS Sensor                                                                                                                                                                               |
| Strømforbrug    | : | DC 12 Max:7.53W(IR ON), 2.28W(IR OFF)                                                                                                                                                                                  |
| Weight          | : | 2,25Kg                                                                                                                                                                                                                 |





**DANBIT**

KAM-2M-STEEL

## SPECIFICATIONS



Danbit A/S Schous plass 1 Oslo, N-0552  
Norway



67 104 460



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.