

19" High Brightness Modular Panel PC with 8th Gen. Intel® Core™ U Series Processor

FEATURES

- 19" TFT-LCD, 1280 x 1024 (SXGA)
- Brightness: 1,600 nits
- Intel® Core™ I3-8145ue Dual Core Processor (standard)
- Intel® Core™ I5-8365 quad Core Processor (option)
- 2x DDR4 SO-DIMM Socket, Supports Up to 2400MHz, 64GB
- Integrated USB 3.2 Gen 2 supports up to 10Gbps
- M.2 E Key Socket for Wireless Module or Intel CRF Module
- Supports Ignition Sensing Function (IGN) (option)
- Wide Range Operating Temperature -20°C to 70°C
- Designed with Rugged Aluminum Die-casting Front Bezel
- Flat IP65 Compliant Front Panel Protection
- Panel / VESA / Rack Mounting
- 9~48VDC via 3-pin Terminal Block



SPECIFICATIONS

Operating Temp.	:	-20°C to 70°C
Andet	:	Fanless Design
DIO	:	16x Isolated DIO (8x DI/8x DO), 20-Pin Terminal Block
Forsyning	:	9~48VDC via 3-pin Terminal Block
Grafik	:	Integrated Intel® UHD Graphics 620
Hukommelse	:	2x DDR4 2400 MHz 260-Pin SO-DIMM Socket Supports up to 64 GB (un-buffered and non-ECC)
IP-Tæthed	:	IP65 Compliant Front Panel
Kontrast	:	1000 : 1
Lysstyrke	:	up to 1,600 nits
Netværk	:	2x GbE LAN, RJ45 - GbE1: Intel I219LM - GbE2: Intel I210
OS SUPPORT	:	Windows® 10, Linux: Supports by project
Porte	:	4x RS-232/422/485 with Auto Flow Control (Supports 5V/12V), DB9



SPECIFICATIONS

Udvidelser	:	2x Full-size Mini-PCle Socket, 1x M.2 2230 E Key, 1x Front Accessible, 4x Antenna Hole SIM
Weight	:	9.2 kg
Dimensioner	:	(WxDxH): 510 x 389.3 x 76 mm

