

MON32-IP66-1N-STEEL

32" IP66 TFT display 6 sides IP66 tight, Optical Bonded, PCAP touch, 1000 nits in stainless steel FEATURES

- 32" TFT 1920x1080@60Hz FULL HD
- PCAP Touch
- 16:9
- 1000 Nits
- Optical Bonded - very important feature
- No condensation behind the front glass
- Improved reliability and performance
- 6-sided fully IP66 sealed
- VGA and HDMI inputs
- UV protection
- Stainless
- VESA Mount 200x200/400x400mm
- Input voltage DC: 12V
- Optional purchase options DC9 -36V / AC110-230V
- CE, ROHS



Danbit A/S Schous plass 1 Oslo, N-0552
Norway



67 104 460



salg@danbit.dk

SPECIFICATIONS

Operating Temp.	:	Operating: 0°C to 60°C Storage: -20°C to 60°C
Approval	:	CE, ROHS
Betjening	:	OSD-Multi Language
Forsyning	:	Input Voltage DC: 12V (Options DC36-9V/AC110-230V)
I/O	:	VGA, HDMI
IP-Tæthed	:	IP66
Kontrast	:	1000:1
Materiale	:	Stainless Steel
Opløsning	:	1920x1080 @60Hz
Touch	:	PCAP
VESA standard	:	200x200mm, 400x400mm

