

21.5" Medical Premium Windows Touch Panel PC Celeron,i3,i5,i7,16:9, PCAP touch, Medical Certificate FEATURES

- CPU support Celeron, i3, i5, i7 Gen.8
- Max. 32GB RAM
- 21.5" True-Flat
- 16:9 Ratio
- 1920x1080 pixel
- PCAP touch USB
- Wifi
- BT
- 2 x RJ45
- 4 x USB3.0
- 1 x RS232, 1xRS232(5v/12v support)/422/485
- 1 x HDMI, 1 x DVI-D
- Ultra Slim 49.9mm with 3 Pieces Design
- Fanless & Front Panel IP65
- Simple Installation & Easy Assembly
- Industrial Quality & Chic Appearance
- Support TPM and Intel vPro (Optional)
- Magnetic I/O Port Cover For Easy Maintaining (Optional)
- Extensional Power Button (Optional)
- TPM
- 9~36Vdc
- 543x334x49.9 mm
- OS support: Win10, Win 11, Linux



SPECIFICATIONS

CPU	:	Intel Core i5 Processor: i5-8365UE vPro Intel Core i7 Processor: i7-8665UE vPro (optional) Intel Core i3 Processor: i3-8145UE (optional) Intel Celeron Processor : 4305UE (optional)
USB	:	4 x USB3.0
Farve	:	Black, Silver, Black / White, Silver, White, need to be specified when ordering
Approval	:	FCC Class B, CE Mark, CB, ICE60601
Ethernet	:	2x RJ45, Intel I219LM (Phy); Intel I211 (PCIe)
Forsyning	:	support 9-36V DC-in, Power adapter 90W/19V, 3-pin
Grafik	:	Intel UHD
Hukommelse	:	2 x S.O.DIMM, DDR4 2400MHz, 8GB (Up to 32GB)
IP-Tæthed	:	IP65 on the front
Kamera	:	2M WebCam (HD webcam, USB interface)
Luftfugtighed	:	Operating 20% - 80% RH non-condensing
Lyd	:	Realtek ALC662VDO-GR



SPECIFICATIONS

Opløsning	:	1920 x 1080 ; 16:9
OS SUPPORT	:	Windows 10, Windows 11, Linux
Porte	:	1 x DB9 (RS232), 2 x DB9 (RS232/422/485)-(RS232 support 5V/12V)
Skærm	:	21.5" LVDS I/F
Touch	:	True-Flat PCAP touch, USB I/F
Udgange	:	1xHDMI, 1xDVI-D
VESA standard	:	Vesa mount 100x100
Dimensioner	:	543 x 334 x 49.9 mm

