

MON21.5-T-IP69K

## 21.5" IP69K stainless PCAP chassis monitor for food and chemical industry, option 1000 nits

### FEATURES

- 21.5", FULL HD 1920 x 1080 16.7m Colors
- Brightness 250nits (Possibility: 1000nits)
- IP69K
- VGA, (Possibility HDMI)
- USB for touch screen control
- PCAP Projected capacitive multitouch screen, touch with flat design
- A true flat, easy to clean front surface with edgeto-edge design
- Full IP69K waterproof enclosure
- SUS 316/ AISI 316 stainless steel for food and chemical industries
- Waterproof sealed conduit pipe for cable protection
- Support VESA / YOKE mount
- Optical bonding (Possibility)
- Operation temperature 0°C to 45°C
- 541 x 337 x 56.2 mm
- 12V DC



Danbit A/S Schous plass 1 Oslo, N-0552  
Norway



67 104 460



salg@danbit.dk

## SPECIFICATIONS

|                 |   |                                         |
|-----------------|---|-----------------------------------------|
| USB             | : | 1x USB typeA for touch screen control   |
| Operating Temp. | : | 0°C to 45°C                             |
| Approval        | : | CE, FCC                                 |
| Forsyning       | : | 12V DC                                  |
| IP-Tæthed       | : | IP rating Full IP65/IP69K               |
| Kontrast        | : | 3000:1                                  |
| Luftfugtighed   | : | 10% to 90% RH, NonCondensing            |
| Maks. opløsning | : | 1920 x 1080                             |
| Materiale       | : | Stainless Housing                       |
| Montering       | : | Vesa; Yoke                              |
| Touch           | : | Projected Capacitive Multi Touch Screen |
| VGA             | : | 1                                       |



**DANBIT**

MON21.5-T-IP69K

## SPECIFICATIONS

Dimensioner : 541 x 337 x 56.2 mm



Danbit A/S Schous plass 1 Oslo, N-0552  
Norway



67 104 460



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.