

Wi-Fi 6 Dual Band Wireless Access Point 3000Mbps with PoE and 2 LAN Ports

FEATURES

- Dual Band 802.11ax 3000Mbps Ceiling-mount Wireless Access Point
- Max. wireless speed of 2400Mbps (5GHz) & 600Mbps (2.4GHz)
- Supports up to 256 simultaneous client users
- 2 x 10/100/1000BASE-T RJ45 port
- 4 x Internal 4dBi antenna (2.4G x2, 5G x2)
- Modes: AP, Gateway, Repeater
- WPA3 / WPA2 / WPA support
- Ceiling mount
- Dimensions: 185.82 x 185.82 x 36.6 mm
- Supports 48V DC PoE and 12V DC input
- Operating temperature range: -20 to 55°C
- Weight: 380 g



SPECIFICATIONS

LAN	:	2 x 10/100/1000BASE-T RJ45 port
Antal	:	256 clients (200 is suggested, depending on usage)
Antenne	:	4 x Internal 4dBi antenna (2.4G x2, 5G x2)
Båndbredde	:	20MHz, 40MHz, 80MHz, 160MHz
Forsyning	:	48V DC IN, 0.5A, IEEE 802.3at PoE+ (WAN/PoE were changed port) 12V DC IN, 1.5A from DC Jack (5.5 x 2.1mm)
Modes	:	Access Point Gateway Repeater WISP Mesh
Montering	:	Ceiling Mount
Sikkerhed	:	WPA3 Personal, WPA2/WPA3 Personal, WPA2 Personal (AES), WPA2 Personal (TKIP), WPA2 Personal (TKIP+AES), WPA/WPA2 Personal (AES), WPA/WPA2 Personal (TKIP), WPA/WPA2 Personal (TKIP+AES), WPA2 Enterprise, WPA/WPA2 Enterprise
Dimensioner	:	185.82 x 185.82 x 36.6 mm

