

4 port KVM switch, matrix 4K 60Hz HDMI, 2 x USB 3.2,
4 x USB 2 (HID) with USB Roaming, PIP etc.

FEATURES

- 4 port KVM switch / matrix with USB Roaming
- Input HDMI 2.0 x 4 (Single Video x 4 PCs) / USB 3.2 Gen 1 Type B x 4
- Output HDMI 2.0 x 2 (Single Video x 2 PCs) / USB 3.2 Gen 1 Type A x 2 (Rear & Front)
- 4K 4096x2160@60Hz (4:4:4) / 3840x2160@60Hz (4:4:4)
- EDID management
- Support 16:9, 21:9, 32:9 Displays
- Vertical PBP with 2 x 32:9 scaling
- Dual output mode for 2 monitors
- Manual switching, Hotkey switching, Serial commands
- Mouse roaming (mouse cursor moves to another screen/PC)
- Audio jack input
- PSU: 9 - 12VDC included
- Dimensions: 40 x 220 x 130



SPECIFICATIONS

Serial	:	RJ11 x 1 (Baud Rate = 19200bps) 8-Bands Baud Rate Selections Mini USB x 1 (Any Baud Rate)
Operating Temp.	:	0~40°C, Humidity<80%
Forsyning	:	DC 9~12V
Input	:	HDMI 2.0 x 4 (Single Video x 4 PCs) USB 3.2 Gen 1 Type B x 4 Audio Jack in x 4
LED	:	Status x 1 Port Status LED x 4
Modes	:	Picture by Picture Mode Monitor by Monitor Mode (Dual Monitor Mode) (MbM Mode)
Output	:	HDMI 2.0 x 2 (Single Video x 2 PCs) USB 3.2 Gen 1 Type A x 2 (Rear & Front) USB HID Type A x 4 (Rear & Front) Audio Jack out x 1 Audio In x 1 (Embed to Port A)
Resolution	:	4096x2160@60Hz (4:4:4) 3840x2160@60Hz (4:4:4)
Number of Buttons	:	Port Select x 4 Function x 1 Video Swap x 1 Console Swap x 1 Sync x 1
Display	:	Support 16:9, 21:9, 32:9 Displays
Dimensioner	:	40 x 220 x 130mm

