

## Wireless Transmitter/Receiver for HDMI / SDI Video signal

### FEATURES

- 3G-SDI and HDMI Inputs and Outputs
- Transmitter: 1x USB-C (5 VDC) Input
- Receiver: 1x USB-C (5 VDC) Input
- Live Streaming via Mobile Device & App
- Range 152.4m max (Line-of-Sight)
- HDMI/SDI
- 1080p: 60/59.94/50/30/29.97/25/24/23.98
- 1080i: 60/50
- 720p: 60/50
- Operating temp. 0 to 50°C
- Dimensions: 113 x 65 x 29.2mm



## SPECIFICATIONS

|                 |   |                                                                           |
|-----------------|---|---------------------------------------------------------------------------|
| Operating Temp. | : | 0 to 50°C                                                                 |
| Afstand         | : | 500' / 152.4 m (Line-of-Sight)                                            |
| Formater        | : | HDMI/SDI 1080p: 60/59.94/50/30/29.97/25/24/23.98 1080i: 60/50 720p: 60/50 |
| Frekvens        | : | 5 GHz                                                                     |
| Skærm           | : | Transmitter: 1,3" OLED, Receiver: 1,3" OLED                               |
| Strømforsyning  | : | Transmitter: 1 x USB-C (5 VDC) Input Receiver: 1 x USB-C (5 VDC) Input    |
| Dimension       | : | 113 x 65 x 29.2 mm                                                        |
| Weight          | : | 200g                                                                      |

