

USB to 8 x RS232/RS422/RS485 adapter, port-type selector on the back

FEATURES

- Adds eight high-speed RS-232/422/485 serial ports via USB connection
- 2k bytes transmitter and receiver
- Requires no IRQ, DMA, I/O port
- RS-232 max bit rates of up to 1 Mbps
- RS-422/485 maximum bit rates of up to 10 Mbps
- Automatic transmission buffer control for 2-wire RS-485 half-duplex operation
- Biasing and terminating resistors installed on board
- Supported RS-232 signals: DCD, RxD, TxD, DTR, GND, DSR, RTS, CTS, RI
- Supported RS-422 signals: TxD-, TxD+, RxD+, RxD-, GND
- Supported RS-485 4-wire signals: TxD-, TxD+, RxD+, RxD-, GND
- Supported RS-485 2-wire signals: Data-, Data+, GND
- Data Bits: 7/8
- Parity: None, Even, Odd, Mark, Space
- Stop Bit: 1, 2
- Flow Control: Hardware (RTS, CTS), XON/XOFF
- Monitor LEDs for TxD, RxD indicating port status
- Built-in AC to DC switching power supply, 100VAC to 240VAC
- Virtual COM port drivers available for Windows 11, 10, 8.1, 8, 7, Vista, 2003, XP, 2000
- Win Server: 2000 up to 2018, Linux, MAC
- Industrial quality metal case with DIN bracket for DIN rail mounting



SPECIFICATIONS

Andet	:	Leveres m/19" rackmonterings-beslag
Kabel	:	Medfølger ikke, benyt K-USB4AM-BMxx
OS SUPPORT	:	Win 2000, XP, Win7, Win8, Win10 og MAC
Signaler	:	USB 1.1 og RS232/422/RS485
Stik	:	8 x DB9
Strømforsyning	:	Indbygget; tilsluttes 230 VAC

