

ESW10G-M-D

10-port managed switch 8 x 10/100/1000Mbit RJ45.
Fiber 2 x 100/1000Mbit SFP, -40 - +75°C 12-48VDC,
24VAC

FEATURES

- Managed Gigabit switch. 8 x RJ45, 2 x SFP
- 8 x 10/100/1000Mbit with RJ45 connectors
- 2 x 100/1000Mbit to SFP
- Supply voltage: 12 - 48VDC redundant
- Also accepts 24VAC
- Power consumption : max. 10W
- DIN rail bracket
- 1 relay for alerting
- Dimensions: 135 x 88 x 56 mm
- Operating temperature: -40 - +75°C



Danbit A/S Schous plass 1 Oslo, N-0552
Norway



67 104 460



salg@danbit.dk

SPECIFICATIONS

Operating Temp.	:	-40 til +75°C
Fiber	:	2 x 100/1000 Mbit porte til SFP
LED	:	Indikation af on/off, fejl, hastighed, link, og aktivitet med lysdioder
Porte	:	8 x 10/100/1000 Mbit porte med RJ45-stik og automatisk detektering af lige/krydset kabel
Relæ	:	1 relæudgang til alarmering ved strømforsyningsfejl
Strømforsyning	:	Redundant indgang til strømforsyning; 2 x terminalblok til 12 - 48 VDC med polaritetsbeskyttelse eller 24 VAC. Maks. 10 W
Tilbehør	:	Leveres med DIN skinnebeslag, vægbeslag, manual på CD og quickguide
Understøtter	:	Understøtter QoS (Quality of Service), hvor bestemte typer netværkstrafik kan prioriteres højere end andre typer (f.eks. ved maskinstyring eller IP-telefoni). Desuden understøttes VLAN med op til 255 grupper

