

ESW10G8SFP

10-port managed switch 2 x 10/100/1000Mbit RJ45.
Fiber 8 x SFP 100/1000Mbit SFP slot, DIN mounting
12-48VDC and 24VAC

FEATURES

- Managed switch. 8 x SFP, 2 x RJ45 ports
- 8 x fiber ports - 100/1000Base-SX / LX mini-GBIC SFP slots
- 2 x copper ports - 10/100/1000Mbit RJ45
- IP30 enclosure
- DIN rail and wall mounting
- 24:02 48V DC, redundant power
- Can accept 24VAC
- 40 to +75°C operating temperature
- Dimensions: 152 x 107 x 72 mm



Danbit A/S Schous plass 1 Oslo, N-0552
Norway



67 104 460



salg@danbit.dk

SPECIFICATIONS

Operating Temp.	:	-40 til +75°C
Fiber	:	8 x 100/1000 Mbit porte til SFP
IP-Tæthed	:	IP31
LED	:	Indikation af on/off, fejl, hastighed, link, og aktivitet med lysdioder
Porte	:	2 x 10/100/1000 Mbit porte med RJ45-stik og automatisk detektering af lige/krydset kabel.
Relæ	:	1 relæudgang til alarmering ved strømforsyningsfejl
Strømforsyning	:	Redundant indgang til strømforsyning; 2 x terminalblok til 12 - 48 VDC eller 24 VAC med polaritetsbeskyttelse.
Tilbehør	:	Leveres med DIN skinnebeslag, vægbeslag, manual på CD og quickguide
Understøtter	:	Understøtter QoS (Quality of Service), hvor bestemte typer netværkstrafik kan prioriteres højere end andre typer (f.eks. ved maskinstyring eller IP-telefoni). Desuden understøttes VLAN med op til 255 grupper
Dimensioner	:	152 x 72 x 107 mm (H x B x D)

