



# DANBIT

ETH1SER-B

1 serialportserver port RS232 / RS485. Serial Device Server

## FEATURES

- Serial device server with RS232 / RS485
- RS232 via DB9
- RS485 via screw terminal - 2-wire



Danbit A/S Schous plass 1 Oslo, N-0552  
Norway



67 104 460



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.

**SPECIFICATIONS**

|                 |   |                                                                                                                                                     |
|-----------------|---|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| CPU             | : | 16 bit CPU, 100 MHz                                                                                                                                 |
| Operating Temp. | : | 0 - 50 °C                                                                                                                                           |
| Hukommelse      | : | 768 KB RAM, 256 KB ROM                                                                                                                              |
| Kabinet         | : | Stålkabinet i format 22 x 67 x 93 mm. (H x B x D)                                                                                                   |
| Netværk         | : | 1 x 10/100 Mbit Ethernet - med autotetektering af hastighed                                                                                         |
| Porte           | : | Én port, der kan bruges som RS232 eller RS485; 1200 bps - 230 Kbps                                                                                  |
| Protokol        | : | TCP, UDP, DHCP, HTTP, ICMP, ARP, ICMP, Telnet                                                                                                       |
| Signaler        | : | RS232: Rx, Tx, RTS, CTS, DTR, DSR og DCD. RS485: Data+ og Data- (2-leder halv duplex)                                                               |
| Skærm           | : | 4 lysdioder viser Tx, Rx, netværks- og systemstatus                                                                                                 |
| Spænding        | : | Kræver 9 - 30 VDC maks. 300 mA (ustabiliseret). Netadapter medfølger                                                                                |
| Stik            | : | DB9-han til RS232. Skrueterminaler til 2-tråds RS485. 1 x RJ45 til Ethernet. Spændingsforsyning: 1 x 5,5 mm. DC jackstik til medfølgende netadapter |

