

6 x Digital input, 6 x Relay output via Ethernet for industrial control applications. 2 x RJ45 daisy chain PoE

FEATURES

- 6 x Digital Inputs - Wet (active at DC in)
- 6 x Power relay outputs - 24VDC / 250VAC / 5A
- Protocol: Modbus TCP / UDP
- 2 x RJ45 Ethernet interface
- With built-in network switch - with the daisy chain I / O Pair-function - the input is mirrored to the second output
- Digital inputs with counter - max 500Hz
- the minimum pulse width: 1 ms
- Screw terminal
- Supply voltage: PoE or 10 - 30VDC / 3watt
- PoE is NOT continued to LAN port 2 (data only)



SPECIFICATIONS

Forsyning	:	10 - 30 VDC, 2,5 W via klemrække eller PoE
Indgang	:	6 stk. digitale Logisk 0: 0 - 4 VDC, Logisk 1: 10 - 50 VDC
Netværk	:	10/100 Mbit m/RJ45-stik
Protokol	:	Modbus/TCP, TCP/IP og UDP
Tæller	:	Indgange kan virke som 32 bit tæller, maks. frekvens 500 Hz
Udgange	:	6 stk. relæudgange: AC: 250 V og 5 A eller DC: 30 V og 5 A. Skiftetider Lukke/åben er 7ms / 3 ms

