

7 x inputs for temperature sensors (differential),
Pt100, Pt1000, Ni120, CU100, CU1000, 1 x RJ45 LAN,
MODBUS, 10-30VDC

FEATURES

- Built-in Web server
- Web HMI
- Modbus TCP and Modbus UDP protocols
- Good communication security
- 1 x RJ45 port Ethernet
- Dual Watchdog
- Operating temperature range: -25 to + 75 ° C
- I / O Pair-connection input is mirrored in the other's output
- 7 x RTD Interface: Pt100, Pt1000, Ni120, CU100, CU1000
- Differentialindgange to the temperature sensor, 2 and 3-wire solution
- 16bit
- Supply voltage: 10 - 30VDC / 2.5watt



SPECIFICATIONS

Forsyning	:	10 - 30 VDC, 5 W via klemrække
Indgang	:	7 stk. differentialindgange (2- eller 3-tråds). Kan bruges med termoføler af typerne Pt, Balco og Ni RTD
Indgangsimpedans	:	10 k Ω
Maks. hastighed	:	10 samples/sekund
Netværk	:	10/100 Mbit m/RJ45-stik
Nøjagtighed	:	maks. $\pm 0,005$ %
Opløsning	:	16 bits
Protokol	:	Modbus/TCP, TCP/IP og UDP

