

KAM-U-BUL2MP

Utendørs 2MP IP Bullet Camera IR, med bredt
dynamisk område. 2,7 - 12mm linse. PoE eller 12VDC.
FEATURES

1/2.8" Scan CMOS
2,7 - 12mm Motorlinse
2MP (1920 × 1080)
IR (Nattvisjon) Opptil 30 meter
IP67 Outdoors. Med Shields
Point Visning: 105 - 32 grader
H.265, H.264, MJPEG
PoE eller 12VDC
Driftstemperatur: -40 ° C ~ 60 ° C
Dimensjoner: 264.5 × 82.7 × 80.3 mm
Vekt: 830 g



Danbit A/S Schous plass 1 Oslo, N-0552
Norway



67 104 460



salg@danbit.dk

SPECIFICATIONS

Driftstemperatur	:	-40°C ~ 60°C
Billede	:	1/2.8" Progressive Scan CMOS
Ethernet	:	1 Ethernet (10/100 Base-T) RJ-45 Connector
Forsyning	:	POE, 12VDC
Funktioner	:	True WDR-12dB
Kamera	:	IR afstand op til 30 meter
Linse	:	Motor linse
Opløsning	:	Maks. 1080P(1920×1080)
OS SUPPORT	:	IOS, Android. virker på internet explorer, chrome, firefox
Pixels	:	1920(H)×1080(V)
Protokol	:	IPv4/IPv6, 802.1x, HTTP, HTTPS, TCP/IP, UDP/IP, RTSP, DHCP, NTP, RTCP/RTP, PPPoE, SMTP, DNS, UPnP, FTP, ARP, SNMP
Strømforbrug	:	3W (IR LED OFF), 8W (IR LED ON)



**DANBIT**

KAM-U-BUL2MP

SPECIFICATIONS

Dimensioner : 264.5×82.7×80.3mm



Danbit A/S Schous plass 1 Oslo, N-0552
Norway



67 104 460



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.