

10.1" LCD Touch Screen Alu Front, Projected
Capacitive touch 1280x800 16:10, IP66 Front, DC 9 ~
36V

FEATURES

10.1" TFT 1280x800 (16:10)
Frontpanel IP66 Standard / IP69K Alternativ
Aluminiumskap
VGA, DVI, HDMI og DP Input
Supply Spenning: DC 9 ~ 36V
KONTRAST: 800: 1
Lysstyrke: 350 Nits Standard / 1000 Nits Alternativ
Touch via USB: Projisert Kapasitiv standard /
Resistivt alternativ / Ingen Touch alternativ
Touch via RS232: Alternativ
VESA 100 og Panel Mount
Dimensjoner: 285 x 189 x 48,9 mm
Vekt: 1,9 kg
Driftstemperatur: 0 ~ +50°C Standard / -20 ~
+60°C Alternativ



SPECIFICATIONS

Annen	:	15G peak acceleration (11 msec. duration) / Operation
Drivere	:	eGalaxTouch
Forsyning	:	DC 9 ~ 36V
Indgang	:	USB
IP-Tæthed	:	IP66 front
Kabinet	:	Aluminum die-casting chassis
Montering	:	Panel and VESA
Opløsning	:	1280x800 16:10
OS SUPPORT	:	Windows XP, Vista, 7, 8, CE, Mac og Linux
Touch	:	USB, PCAP
VESA standard	:	100 x 100mm
Vekt	:	1.9 kg



**DANBIT**

MON10.1-TFT-T

SPECIFICATIONS



Danbit A/S Schous plass 1 Oslo, N-0552
Norway



67 104 460



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.