

## ADLINK PCI-7230. 16 kanalers isolerede digitale input, 16 kanalers isolerede digitale OC-output , PCI NEW!

### FEATURES

- 16 optoisolerede indgange, fælles stel (minus) og 16 optoisolerede udgange,
- Supports a 32-bit 5 V PCI bus
- 16-CH isolated digital inputs
- 16-CH isolated digital outputs - Open-Collector
- 5000 VRMS optical isolation
- Sink current up to 500 mA on each isolated output



**SPECIFICATIONS**

|                  |   |                                                                                                   |
|------------------|---|---------------------------------------------------------------------------------------------------|
| Indgang          | : | 16 optoisolerede, fælles stel (minus) Logisk 0: 0-1,5 VDC Logisk 1: 5-24 VDC                      |
| Indgangsimpedans | : | 1,2 kΩ / 0,5 W                                                                                    |
| Isolation        | : | 2.500 VDC på ind- og udgange                                                                      |
| Software         | : | Drivere til Windows 2000, XP, Win7 og Win8 Labview og Linux medfølger                             |
| Stik             | : | DB37 hun                                                                                          |
| Udgange          | : | 16 optoisolerede, fælles stel (minus) "Open collector" 5-35 VDC Kan trække op til 500 mA til stel |
| Dimensioner      | : | 69 x 120 mm                                                                                       |

